

屋内照明器具特性

品番 (品名)	LSEB1162K															
光源	LED6200_70_4500 x1 4500.0 lm															
管理番号	K0183775(0)D 1															
BZ分類	BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%	室指数																			
下方光束	96%	照明率 (X0.01)																			
保守率	良 0.63 中 0.6 否 0.56	ZCM																			
下方投影面積	c m ²	1.25	56	43	36	30	54	43	35	30	51	41	35	30	49	40	34	29	27		
等価発光面積		c m ²	1.5	66	54	46	40	64	53	46	40	61	51	45	39	58	49	44	39	36	
取付高さ	器具間隔最大限		2.5	72	61	53	48	70	60	53	47	67	58	52	47	63	56	50	46	43	
	横方向 (A)	縦方向 (B)	3.0	78	68	61	55	76	67	60	55	72	65	58	54	69	62	57	53	50	
H m	1.26 H m	1.26 H m	4.0	82	73	66	60	80	72	65	60	76	69	64	59	73	67	62	58	55	
			5.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62	
			7.0	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	70	67	
			10.0	94	88	83	79	92	86	82	78	88	83	79	76	84	81	77	74	71	
				97	92	88	84	95	91	87	83	91	88	84	81	88	85	82	79	76	
				99	95	91	88	97	93	90	87	93	90	87	85	90	87	85	83	79	
				101	98	95	93	99	97	94	92	96	93	91	89	92	90	89	87	83	
				103	101	99	97	101	99	97	95	98	96	94	93	94	93	91	90	86	

