

# 屋内照明器具特性

|         |                    |  |  |  |  |           |  |  |  |  |
|---------|--------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | LGB51355K          |  |  |  |  |           |  |  |  |  |
| 光源      | LED5000_70_1285 x1 |  |  |  |  | 1285.0 lm |  |  |  |  |
| 管理番号    | K0154731(0)DB1     |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ5/0.7/BZ4        |  |  |  |  |           |  |  |  |  |

|        |         |         |               |     |     |     |     |     |     |     |     |     |    |    |     |     |    |    |     |    |
|--------|---------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|----|-----|----|
| 器具効率   | 100%    | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |     |    |    | 0%  |    |
|        |         |         | 壁             | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 0% |
| 上方光束   | 0%      | 反射率     | 10%           |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |     |    |    | 0%  |    |
| 下方光束   | 100%    |         | 床             | 10% |     |     |     | 10% |     |     |     | 10% |    |    |     | 10% |    |    |     | 0% |
|        |         | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |    |    |     |     |    |    | ZCM |    |
| 保守率    | 良       | 0.69    | 0.6           | 58  | 46  | 38  | 33  | 57  | 45  | 38  | 33  | 54  | 44 | 37 | 33  | 52  | 43 | 37 | 32  | 31 |
|        | 中       | 0.67    | 0.8           | 68  | 57  | 49  | 43  | 66  | 56  | 49  | 43  | 64  | 55 | 48 | 43  | 61  | 53 | 47 | 43  | 41 |
|        | 否       | 0.63    | 1.0           | 75  | 64  | 57  | 51  | 73  | 63  | 56  | 51  | 70  | 62 | 55 | 51  | 68  | 60 | 55 | 50  | 48 |
|        |         |         | 1.25          | 81  | 71  | 64  | 59  | 79  | 70  | 64  | 58  | 76  | 69 | 63 | 58  | 73  | 67 | 62 | 58  | 55 |
| 下方投影面積 |         |         | 1.5           | 85  | 76  | 70  | 64  | 83  | 75  | 69  | 64  | 80  | 73 | 68 | 63  | 77  | 72 | 67 | 63  | 61 |
|        |         |         | 2.0           | 90  | 83  | 77  | 73  | 89  | 82  | 77  | 72  | 86  | 80 | 75 | 71  | 83  | 78 | 74 | 71  | 68 |
| 取付高さ   | 器具間隔最大限 |         | 2.5           | 94  | 88  | 83  | 78  | 92  | 87  | 82  | 78  | 89  | 84 | 80 | 77  | 86  | 82 | 79 | 76  | 73 |
|        | 横方向 (A) | 縦方向 (B) | 3.0           | 96  | 91  | 86  | 82  | 95  | 90  | 86  | 82  | 92  | 88 | 84 | 81  | 89  | 86 | 83 | 80  | 77 |
| 1.5m   | 1.86m   | 1.98m   | 4.0           | 99  | 95  | 91  | 88  | 98  | 94  | 90  | 87  | 95  | 92 | 89 | 86  | 92  | 90 | 87 | 85  | 82 |
| 2      | 2.46    | 2.55    | 5.0           | 101 | 98  | 94  | 92  | 99  | 96  | 94  | 91  | 97  | 94 | 92 | 90  | 94  | 92 | 90 | 88  | 85 |
| 2.5    | 3.06    | 3.15    | 7.0           | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97 | 95 | 94  | 97  | 95 | 93 | 92  | 89 |
| 3      | 3.66    | 3.74    | 10.0          | 105 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 99 | 98 | 97  | 98  | 97 | 96 | 95  | 92 |

