

屋内照明器具特性

品番 (品名)	NWCF 59016									
光源	LED2700_70_570 ×1					570.0 lm				
管理番号	K0185149 (0) DR 1									
BZ分類	BZ6/3.5/BZ7/4.5/BZ6/6.0/BZ7									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 49%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	51%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	48	36	29	23	44	34	27	22	37	29	23	19	30	24	20	16	11	
	中	0.63	0.8	56	45	37	31	52	42	34	29	43	35	30	26	36	30	25	22	15	
	否	0.56	1.0	62	51	43	37	57	47	40	35	48	40	35	30	39	34	29	26	18	
			0.56	1.25	67	57	49	44	62	53	46	41	52	45	40	35	43	38	33	30	21
下方投影面積			c m ²	1.5	71	62	54	49	66	57	51	45	55	49	44	39	45	41	37	33	23
等価発光面積			c m ²	2.0	76	68	62	56	71	63	57	52	59	54	49	45	49	45	41	38	27
取付高さ	器具間隔最大限		H m	2.5	80	73	67	61	74	67	62	57	62	57	53	50	52	48	45	42	30
	横方向 (A)	縦方向 (B)		3.0	82	76	70	66	76	70	66	61	64	60	56	53	53	50	47	45	32
	0.79 H m	1.62 H m	4.0	85	80	76	71	79	75	70	67	67	64	60	57	56	53	51	49	35	
			5.0	88	83	79	75	81	77	74	70	69	66	63	61	58	55	53	51	37	
			7.0	90	86	83	80	84	80	78	75	71	69	67	65	60	58	56	55	40	
			10.0	92	89	87	84	86	83	81	79	73	71	70	68	62	60	59	58	42	

