

# 屋内照明器具特性

|         |                 |          |
|---------|-----------------|----------|
| 品番 (品名) | NTN88006BK      |          |
| 光源      | LLD3020MLCB1 ×1 | 715.0 lm |
| 管理番号    | K0175527(0)DR1  |          |
| BZ分類    | BZ1             |          |

|                  |                 |             |      |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
|------------------|-----------------|-------------|------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|
| 器具効率             | 73%             | 天井          | 80%  |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0% |    |
|                  | 上方光束            |             | 0%   | 70 | 50 | 30 | 10  | 70 | 50 | 30 | 10  | 70 | 50 | 30 | 10  | 70 | 50 | 30 | 10 | 0% |
| 下方光束             | 73%             | 床           | 10%  |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0% |    |
| 室指数              |                 | 照明率 (X0.01) | ZCM  |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |    |    |
| 保守率              | 良               | 0.67        | 0.6  | 60 | 56 | 53 | 51  | 60 | 55 | 53 | 51  | 59 | 55 | 52 | 51  | 58 | 54 | 52 | 50 | 50 |
|                  | 中               | 0.63        | 0.8  | 65 | 60 | 58 | 56  | 64 | 60 | 58 | 56  | 63 | 60 | 57 | 55  | 62 | 59 | 57 | 55 | 54 |
|                  | 否               | 0.56        | 1.0  | 67 | 64 | 61 | 59  | 67 | 63 | 61 | 59  | 65 | 63 | 60 | 59  | 64 | 62 | 60 | 58 | 57 |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25        | 70   | 66 | 64 | 62 | 69  | 66 | 64 | 62 | 68  | 65 | 63 | 62 | 66  | 64 | 63 | 61 | 60 |    |
|                  |                 | 1.5         | 71   | 68 | 66 | 64 | 70  | 68 | 66 | 64 | 69  | 67 | 65 | 64 | 68  | 66 | 64 | 63 | 62 |    |
|                  |                 | 2.0         | 73   | 71 | 69 | 67 | 72  | 70 | 68 | 67 | 71  | 69 | 68 | 66 | 70  | 68 | 67 | 66 | 64 |    |
| 取付高さ             | 器具間隔最大限         |             | 2.5  | 74 | 72 | 71 | 69  | 73 | 72 | 70 | 69  | 72 | 70 | 69 | 68  | 71 | 69 | 68 | 67 | 66 |
|                  | 横方向 (A)         | 縦方向 (B)     | 3.0  | 75 | 73 | 72 | 71  | 74 | 73 | 71 | 70  | 73 | 71 | 70 | 69  | 71 | 70 | 69 | 68 | 67 |
| Hm               | 0.41Hm          | 0.41Hm      | 4.0  | 76 | 75 | 73 | 72  | 75 | 74 | 73 | 72  | 74 | 73 | 72 | 71  | 72 | 71 | 71 | 70 | 68 |
|                  |                 |             | 5.0  | 76 | 75 | 74 | 73  | 76 | 75 | 74 | 73  | 74 | 73 | 73 | 72  | 73 | 72 | 71 | 71 | 69 |
|                  |                 |             | 7.0  | 77 | 76 | 76 | 75  | 76 | 76 | 75 | 74  | 75 | 74 | 74 | 73  | 73 | 73 | 72 | 72 | 70 |
|                  |                 |             | 10.0 | 78 | 77 | 76 | 76  | 77 | 76 | 76 | 75  | 75 | 75 | 74 | 74  | 74 | 73 | 73 | 73 | 71 |

