

屋内照明器具特性

品番 (品名)	NTN88006BK				
光源	LLD4000LCS1 ×1 830.0 lm				
管理番号	K0181861(0)DR1				
BZ分類	BZ4/0.9/BZ3				

器具効率	54%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%	室指数																		
下方光束	54%	照明率 (×0.01)																		
		ZCM																		
保守率	良	0.67	0.6	3.2	2.6	2.2	2.0	3.2	2.6	2.2	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	2.0	1.9
	中	0.63	0.8	3.8	3.2	2.9	2.6	3.7	3.2	2.8	2.6	3.6	3.1	2.8	2.6	3.5	3.1	2.8	2.6	2.4
	否	0.56	1.0	4.2	3.6	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.8	3.5	3.2	3.0	2.9
			1.25	4.5	4.0	3.7	3.4	4.4	4.0	3.7	3.4	4.2	3.9	3.6	3.4	4.1	3.8	3.6	3.4	3.2
下方投影面積		cm ²	1.5	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	4.4	4.1	3.9	3.7	4.3	4.0	3.8	3.6	3.5
等価発光面積		cm ²	2.0	4.9	4.6	4.3	4.1	4.9	4.6	4.3	4.1	4.7	4.5	4.2	4.1	4.6	4.4	4.2	4.0	3.9
取付高さ	器具間隔最大限		2.5	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.8	4.6	4.4	4.3	4.1
	横方向 (A)	縦方向 (B)	3.0	5.2	5.0	4.8	4.6	5.2	4.9	4.7	4.6	5.0	4.8	4.7	4.5	4.9	4.7	4.6	4.5	4.3
H _m	1.26H _m	1.26H _m	4.0	5.4	5.2	5.0	4.9	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.8	5.0	4.9	4.8	4.7	4.6
			5.0	5.5	5.3	5.2	5.0	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.7
			7.0	5.6	5.4	5.3	5.2	5.5	5.4	5.3	5.2	5.3	5.3	5.2	5.1	5.2	5.1	5.1	5.0	4.9
			10.0	5.6	5.5	5.5	5.4	5.6	5.5	5.4	5.3	5.4	5.4	5.3	5.2	5.3	5.2	5.2	5.2	5.0

