

屋内照明器具特性

品番 (品名)	NTN88006BK															
光源	LLD2000LCS1 ×1 580.0 1m															
管理番号	K0181862 (0) DR 1															
BZ分類	BZ4 / 0.9 / BZ3															

器具効率	52 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	52 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	31	25	22	19	31	25	22	19	29	25	21	19	28	24	21	19	18		
		0.8	37	31	28	25	36	31	27	25	35	30	27	25	33	30	27	25	24		
		1.0	40	35	32	29	39	35	31	29	38	34	31	29	37	33	31	29	28		
		1.25	43	39	35	33	42	38	35	33	41	37	35	33	40	37	34	32	31		
下方投影面積	c m ²	1.5	45	41	38	36	44	41	38	36	43	40	37	35	42	39	37	35	34		
		2.0	48	45	42	40	47	44	42	40	46	43	41	39	44	42	40	39	38		
取付高さ	器具間隔最大限		2.5	49	47	44	42	49	46	44	42	47	45	43	42	46	44	43	41	40	
	横方向 (A)	縦方向 (B)	3.0	50	48	46	44	50	48	46	44	48	47	45	44	47	46	44	43	42	
H m	1.26 H m	1.26 H m	4.0	52	50	48	47	51	49	48	47	50	48	47	46	48	47	46	45	44	
			5.0	53	51	50	49	52	51	49	48	51	49	48	47	49	48	48	47	45	
			7.0	54	52	51	50	53	52	51	50	52	51	50	49	50	50	49	48	47	
			10.0	54	53	53	52	54	53	52	52	52	52	51	51	51	51	50	50	48	

