

屋内照明器具特性

品番 (品名)	NTN88006WK		
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 1 m		
管理番号	K0183944 (0) DR 1		
BZ分類	BZ1		

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床		10%				10%				10%				10%				0%
室指数	照明率 (X 0.01)																			ZCM
保守率	良 0.67	0.6	76	69	64	61	75	68	64	61	74	68	63	60	72	67	63	60	59	
	中 0.63		84	77	73	69	83	77	72	69	81	76	72	69	79	75	71	69	67	
	否 0.56		88	82	78	75	87	82	78	75	85	81	77	74	84	80	77	74	73	
下方投影面積 等価発光面積	c m ²	1.25	92	87	83	80	91	86	83	80	89	85	82	79	87	84	81	79	77	
		1.5	94	90	86	84	93	89	86	83	91	88	85	83	90	87	84	82	80	
取付高さ	器具間隔最大限		2.5	99	96	94	91	98	95	93	91	96	94	92	90	94	92	91	89	87
	横方向 (A)	縦方向 (B)	3.0	101	98	96	94	99	97	95	93	97	95	94	92	95	94	92	91	89
H m	0.75 H m	0.75 H m	4.0	102	100	98	97	101	99	97	96	99	97	96	95	97	96	94	93	91
			5.0	103	101	100	98	102	100	99	98	100	98	97	96	98	97	96	95	92
			7.0	104	103	102	101	103	102	101	100	101	100	99	98	99	98	97	96	94
			10.0	105	104	103	102	104	103	102	101	101	100	100	99	99	98	98	95	95

