

屋内照明器具特性

品番 (品名)	XNW2062WV	
光源	LED3500_85_1875 ×1	1875.0lm
管理番号	K0183311(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM
保守率	良 0.81	0.6	85	79	75	72	84	78	75	72	83	78	74	72	81	77	74	72	71		
	中 0.77		0.8	91	85	82	79	90	85	81	79	88	84	81	79	87	83	81	78	77	
	否 0.68		1.0	94	90	86	84	93	89	86	84	92	88	85	83	90	87	85	83	82	
下方投影面積	cm ²	1.25	97	93	90	88	96	92	90	87	95	91	89	87	93	90	88	86	85		
		1.5	99	95	93	90	98	95	92	90	96	93	91	89	95	92	90	89	87		
等価発光面積	cm ²	2.0	101	98	96	94	100	98	95	94	99	96	94	93	97	95	93	92	90		
		2.5	103	100	98	97	102	100	98	96	100	98	96	95	98	96	95	94	92		
取付高さ	器具間隔最大限		3.0	104	102	100	98	103	101	99	98	101	99	98	96	99	98	96	93		
	横方向 (A)	縦方向 (B)	4.0	105	103	102	100	104	102	101	100	102	101	99	98	100	99	98	95		
Hm	0.79Hm	0.79Hm	5.0	106	104	103	102	105	103	102	101	102	101	101	100	101	100	99	96		
			7.0	107	105	105	104	105	104	104	103	103	102	102	101	101	100	99	97		
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	100	98		

