

屋内照明器具特性

品番 (品名)	SNCX31120														
光源	LED6200_70_4299 x1 4299.0 lm														
管理番号	K0182582(0)D 1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	6%	室指数	照明率 (X0.01)																ZCM		
下方光束	94%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	55	43	35	29	53	42	34	29	50	40	33	29	48	39	33	28	26		
		0.8	65	53	45	39	63	52	45	39	59	50	43	38	56	48	42	38	35		
		1.0	71	61	53	47	69	59	52	46	66	57	50	45	62	55	49	45	42		
		1.25	77	68	60	54	75	66	59	54	71	64	57	53	68	61	56	51	48		
下方投影面積	c m ²	1.5	82	73	65	60	79	71	64	59	75	68	63	58	72	66	61	57	53		
		2.0	87	80	73	68	85	78	72	67	81	75	70	66	77	72	68	64	61		
取付高さ	器具間隔最大限		2.5	91	84	79	74	89	83	77	73	84	79	75	71	81	76	73	69	66	
	横方向 (A)	縦方向 (B)	3.0	93	88	83	78	91	86	81	77	87	83	79	75	83	79	76	73	69	
H m	1.30 H m	1.30 H m	4.0	97	92	88	84	94	90	86	83	90	87	84	81	86	84	81	78	74	
			5.0	98	95	91	88	96	93	90	87	92	89	87	84	89	86	84	82	78	
			7.0	101	98	95	93	99	96	94	91	95	93	90	89	91	89	87	86	81	
			10.0	103	100	98	97	101	99	97	95	97	95	94	92	93	92	90	89	85	

