

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NSEK47722J + NEL4400LW       |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED4000_85_3500 x1 3500.0 lm |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0193795 (0) DB1             |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4                          |  |  |  |  |  |  |  |  |  |  |

| 器具効率   | 100%    | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |    |    |    | 0%  |    |
|--------|---------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|----|-----|----|
|        |         |         | 壁             | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70 | 50 | 30 | 10  | 0% |
| 上方光束   | 0%      | 床       | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%    | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |    |     |    |    |    | ZCM |    |
| 保守率    | 良       | 0.81    | 0.6           | 60  | 48  | 41  | 36  | 59  | 48  | 41  | 36  | 56  | 47  | 40 | 36  | 54 | 46 | 40 | 35  | 34 |
|        | 中       | 0.77    | 0.8           | 70  | 59  | 52  | 47  | 69  | 59  | 52  | 47  | 66  | 57  | 51 | 46  | 64 | 56 | 51 | 46  | 44 |
|        | 否       | 0.68    | 1.0           | 77  | 67  | 60  | 55  | 75  | 66  | 60  | 55  | 73  | 65  | 59 | 54  | 70 | 63 | 58 | 54  | 52 |
|        |         |         | 1.25          | 83  | 74  | 67  | 62  | 81  | 73  | 67  | 62  | 78  | 71  | 66 | 62  | 76 | 70 | 65 | 61  | 59 |
| 下方投影面積 |         |         | 1.5           | 87  | 79  | 73  | 68  | 85  | 78  | 72  | 67  | 82  | 76  | 71 | 67  | 80 | 74 | 70 | 66  | 64 |
|        | 等価発光面積  |         | 2.0           | 92  | 85  | 80  | 76  | 90  | 84  | 80  | 75  | 88  | 83  | 78 | 75  | 85 | 81 | 77 | 74  | 72 |
| 取付高さ   | 器具間隔最大限 |         | 2.5           | 95  | 90  | 85  | 81  | 94  | 89  | 84  | 81  | 91  | 87  | 83 | 80  | 88 | 85 | 82 | 79  | 76 |
|        | 横方向 (A) | 縦方向 (B) | 3.0           | 97  | 93  | 89  | 85  | 96  | 92  | 88  | 85  | 93  | 90  | 86 | 83  | 91 | 88 | 85 | 82  | 80 |
| 1.5m   | 1.91m   | 2.12m   | 4.0           | 100 | 96  | 93  | 90  | 99  | 95  | 92  | 90  | 96  | 93  | 91 | 88  | 94 | 91 | 89 | 87  | 84 |
| 2      | 2.52    | 2.67    | 5.0           | 102 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 95  | 93 | 91  | 95 | 93 | 92 | 90  | 87 |
| 2.5    | 3.14    | 3.24    | 7.0           | 104 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 96 | 95  | 97 | 96 | 95 | 93  | 91 |
| 3      | 3.75    | 3.82    | 10.0          | 105 | 103 | 102 | 101 | 104 | 102 | 101 | 100 | 101 | 100 | 99 | 98  | 99 | 98 | 97 | 96  | 93 |

