

# 屋内照明器具特性

品番(品名)	LGB15489														
光源	LLD4000LCE1 ×1 845.0 lm														
管理番号	K0185491(0)DR1														
BZ分類	BZ4/0.7/BZ3														

器具効率	79%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 79%	室指数	照明率 ( X0.01 ) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	48	39	33	29	47	39	33	29	45	38	33	29	44	37	33	29	28		
		0.8	57	49	43	39	56	48	43	39	54	47	43	39	52	46	42	39	37		
		1.0	63	55	50	46	62	55	50	46	60	54	49	46	58	53	49	46	44		
		1.25	67	61	56	53	66	60	56	52	64	59	55	52	62	58	55	52	50		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	70	65	60	57	69	64	60	57	67	63	59	56	65	61	58	56	54		
		2.0	74	70	66	63	73	69	66	63	71	68	65	62	69	66	64	61	60		
		2.5	77	73	70	67	76	72	69	66	73	71	68	66	72	69	67	65	63		
取付高さ H m	器具間隔最大限		3.0	78	75	72	70	77	74	71	69	75	73	70	68	73	71	69	66		
	横方向(A) 1.28H m	縦方向(B) 1.28H m	4.0	80	78	75	73	79	77	75	73	77	75	73	72	75	74	72	71	69	
			5.0	81	79	77	76	80	78	77	75	78	77	75	74	76	75	74	73	71	
			7.0	83	81	80	78	82	80	79	78	80	78	77	76	78	77	76	75	73	
			10.0	84	82	81	80	83	82	81	80	81	80	79	78	79	78	77	75	73	

