

屋内照明器具特性	
品番 (品名)	LGB15489
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m
管理番号	K0185502 (0) DR1
BZ分類	BZ3/1.1/BZ2

器具効率	92%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	92%																																																						
保守率	良 0.67 中 0.63 否 0.56	0.6	58	48	42	37	57	48	41	37	55	47	41	37	53	46	41	37	35																																				
		0.8	68	60	54	49	67	59	53	49	65	58	53	49	63	57	52	49	47																																				
		1.0	75	67	62	57	74	66	61	57	71	65	60	57	69	64	60	57	55																																				
		1.25	80	73	68	64	79	73	68	64	77	71	67	64	75	70	66	63	62																																				
下方投影面積	cm ²	1.5	83	77	73	69	82	77	72	69	80	75	71	68	78	74	71	68	66																																				
		2.0	88	83	79	76	86	82	78	75	84	80	77	75	82	79	76	74	72																																				
等価発光面積	cm ²	2.5	90	86	83	80	89	85	82	79	87	84	81	79	85	82	80	78	76																																				
		3.0	92	88	85	83	91	87	85	82	88	86	83	81	86	84	82	80	78																																				
取付高さ	器具間隔最大限		4.0	94	91	89	87	93	90	88	86	90	88	87	85	88	87	85	84	81																																			
	横方向 (A)	縦方向 (B)	5.0	95	93	91	89	94	92	90	88	92	90	89	87	90	88	87	86	83																																			
Hm	1.22Hm	1.22Hm	7.0	96	95	93	92	95	94	92	91	93	92	91	90	91	90	89	88	86																																			
			10.0	97	96	95	94	96	95	94	93	94	93	92	92	92	91	91	90	88	88																																		

