

屋内照明器具特性	
品番 (品名)	S NCX5 1 1 2 0
光源	LED6200_70_5499 x1 5499.0 lm
管理番号	K0182582(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	6%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	5.5	4.3	3.5	2.9	5.3	4.2	3.4	2.9	5.0	4.0	3.3	2.9	4.8	3.9	3.3	2.8	2.6
	中	0.6	0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.5	3.9	5.9	5.0	4.3	3.8	5.6	4.8	4.2	3.8	3.5
	否	0.56	1.0	7.1	6.1	5.3	4.7	6.9	5.9	5.2	4.6	6.6	5.7	5.0	4.5	6.2	5.5	4.9	4.5	4.2
			1.25	7.7	6.8	6.0	5.4	7.5	6.6	5.9	5.4	7.1	6.4	5.7	5.3	6.8	6.1	5.6	5.1	4.8
下方投影面積		cm ²	1.5	8.2	7.3	6.5	6.0	7.9	7.1	6.4	5.9	7.5	6.8	6.3	5.8	7.2	6.6	6.1	5.7	5.3
等価発光面積		cm ²	2.0	8.7	8.0	7.3	6.8	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.6	7.7	7.2	6.8	6.4	6.1
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.9	7.4	8.9	8.3	7.7	7.3	8.4	7.9	7.5	7.1	8.1	7.6	7.3	6.9	6.6
	横方向 (A)	縦方向 (B)	3.0	9.3	8.8	8.3	7.8	9.1	8.6	8.1	7.7	8.7	8.3	7.9	7.5	8.3	7.9	7.6	7.3	6.9
Hm	1.30Hm	1.30Hm	4.0	9.7	9.2	8.8	8.4	9.4	9.0	8.6	8.3	9.0	8.7	8.4	8.1	8.6	8.4	8.1	7.8	7.4
			5.0	9.8	9.5	9.1	8.8	9.6	9.3	9.0	8.7	9.2	8.9	8.7	8.4	8.9	8.6	8.4	8.2	7.8
			7.0	10.1	9.8	9.5	9.3	9.9	9.6	9.4	9.1	9.5	9.3	9.0	8.9	9.1	8.9	8.7	8.6	8.1
			10.0	10.3	10.0	9.8	9.7	10.1	9.9	9.7	9.5	9.7	9.5	9.4	9.2	9.3	9.2	9.0	8.9	8.5

