

屋内照明器具特性

| | | |
|---------|-------------------|-----------|
| 品番 (品名) | XAD5 1 0 1 V | |
| 光源 | LLD5000VCC1 ×1 | 1140.0 lm |
| 管理番号 | K0187675 (2) DR 1 | |
| BZ分類 | BZ2 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-------------|-----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|----|-----|
| 器具効率 | 80% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 0% | | 下方光束 80% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.67 | 0.6 | 53 | 46 | 40 | 37 | 53 | 45 | 40 | 37 | 51 | 44 | 40 | 37 | 50 | 44 | 40 | 37 | 35 | |
| | 中 | 0.63 | 0.8 | 62 | 55 | 50 | 46 | 61 | 54 | 50 | 46 | 59 | 53 | 49 | 46 | 57 | 52 | 49 | 46 | 44 | |
| | 否 | 0.56 | 1.0 | 67 | 61 | 56 | 53 | 66 | 60 | 56 | 53 | 64 | 59 | 55 | 52 | 62 | 58 | 55 | 52 | 51 | |
| | | | 1.25 | 71 | 66 | 61 | 58 | 70 | 65 | 61 | 58 | 68 | 64 | 60 | 58 | 66 | 63 | 60 | 57 | 56 | |
| 下方投影面積 | cm ² | | 1.5 | 74 | 69 | 65 | 62 | 73 | 68 | 65 | 62 | 71 | 67 | 64 | 61 | 69 | 66 | 63 | 61 | 59 | |
| 等価発光面積 | cm ² | | 2.0 | 77 | 73 | 70 | 67 | 76 | 72 | 70 | 67 | 74 | 71 | 69 | 66 | 72 | 70 | 68 | 66 | 64 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 79 | 76 | 73 | 71 | 78 | 75 | 73 | 70 | 76 | 74 | 72 | 70 | 74 | 72 | 70 | 69 | 67 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 80 | 78 | 75 | 73 | 79 | 77 | 75 | 73 | 78 | 75 | 73 | 72 | 76 | 74 | 72 | 71 | 69 | |
| Hm | 1.23Hm | 1.23Hm | 4.0 | 82 | 80 | 78 | 76 | 81 | 79 | 77 | 76 | 79 | 78 | 76 | 75 | 77 | 76 | 75 | 74 | 72 | |
| | | | 5.0 | 83 | 81 | 80 | 78 | 82 | 80 | 79 | 78 | 80 | 79 | 78 | 76 | 78 | 77 | 76 | 75 | 73 | |
| | | | 7.0 | 84 | 83 | 82 | 81 | 83 | 82 | 81 | 80 | 81 | 80 | 79 | 79 | 80 | 79 | 78 | 77 | 75 | |
| | | | 10.0 | 85 | 84 | 83 | 82 | 84 | 83 | 82 | 82 | 82 | 81 | 81 | 80 | 80 | 80 | 79 | 79 | 77 | |

