

屋内照明器具特性

品番 (品名)	XAD3 1 0 8 N	
光源	LLD4000NCE1 ×1	845.0 l m
管理番号	K0187668 (1) DR 1	
B Z 分類	BZ2 / 1.8 / BZ3	

器具効率	66 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	66 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	44	37	33	30	43	37	33	30	42	36	33	30	41	36	32	30	29	
		0.8	50	44	40	37	49	44	40	37	48	43	39	37	47	42	39	37	35	
		1.0	54	49	45	42	53	48	44	42	52	47	44	41	50	46	44	41	40	
		1.25	57	53	49	46	57	52	49	46	55	51	48	46	53	50	47	45	44	
下方投影面積	c m ²	1.5	60	55	52	49	59	55	52	49	57	54	51	49	56	53	50	48	47	
		2.0	63	59	56	54	62	58	56	53	60	57	55	53	58	56	54	52	51	
取付高さ	器具間隔最大限		2.5	64	61	59	57	63	61	58	56	62	59	57	56	60	58	56	55	53
	横方向 (A)	縦方向 (B)	3.0	66	63	61	59	65	62	60	58	63	61	59	58	61	60	58	57	55
H m	1.14 H m	1.14 H m	4.0	67	65	63	62	66	64	63	61	65	63	62	60	63	62	60	59	58
			5.0	68	66	65	63	67	66	64	63	66	64	63	62	64	63	62	61	59
			7.0	69	68	67	66	68	67	66	65	67	66	65	64	65	64	64	63	61
			10.0	70	69	68	67	69	68	67	67	67	67	66	65	66	65	64	64	62

