

# 屋内照明器具特性

品番 (品名)	XAD3 1 2 9 N	
光源	LLD3 0 2 0 NCE1 × 1	795.0 l m
管理番号	K0187670 (1) DR 1	
BZ分類	BZ1	

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	68 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 ( X 0.01 )																ZCM	
保守率	良	0.67	0.6	59	56	53	52	59	55	53	52	58	55	53	52	57	55	53	51	51
	中	0.63	0.8	63	60	57	56	62	59	57	56	61	59	57	56	60	58	57	55	55
	否	0.56	1.0	65	62	60	59	64	62	60	58	63	61	59	58	62	61	59	58	57
下方投影面積	等価発光面積	c m <sup>2</sup>	1.25	67	64	62	61	66	64	62	61	65	63	62	60	64	62	61	60	59
			1.5	68	66	64	63	67	65	64	62	66	64	63	62	65	64	62	61	60
取付高さ	器具間隔最大限		2.0	69	67	66	65	69	67	66	64	67	66	65	64	66	65	64	63	62
	横方向 (A)	縦方向 (B)	2.5	70	69	67	66	69	68	67	66	68	67	66	65	67	66	65	64	63
H m	0.43 H m	0.43 H m	3.0	71	69	68	67	70	69	68	67	69	68	67	66	67	67	66	65	64
			4.0	71	70	69	69	71	70	69	68	69	68	68	67	68	67	67	66	65
			5.0	72	71	70	69	71	70	70	69	70	69	68	68	68	68	67	67	65
			7.0	72	72	71	71	71	71	70	70	70	70	69	69	69	68	68	68	66
			10.0	73	72	72	71	72	71	71	71	70	70	70	69	69	69	68	68	66

