

# 屋内照明器具特性

品番 (品名)	XAS5000L				
光源	LLD5000LCC1 ×1                      1140.0 lm				
管理番号	K0187895(0)DR1				
BZ分類	BZ2				

器具効率	89%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
		床	10%				10%				10%				10%				0%			
上方光束	0%																					
下方光束	89%																					
		室指数	照明率 ( X0.01 )																			ZCM
保守率	良 中 否	0.67	0.6	60	51	45	42	59	51	45	42	57	50	45	41	56	49	45	41	40		
		0.63	0.8	69	61	56	52	68	61	56	52	66	60	55	52	64	59	55	51	50		
			1.0	75	68	63	59	74	67	62	59	72	66	62	58	70	65	61	58	57		
		0.56	1.25	79	73	69	65	78	72	68	65	76	71	67	64	74	70	67	64	62		
下方投影面積			1.5	82	77	72	69	81	76	72	69	79	75	71	68	77	73	70	68	66		
			2.0	86	81	78	75	85	81	77	74	82	79	76	74	80	78	75	73	71		
取付高さ	器具間隔最大限		2.5	88	84	81	79	87	84	81	78	85	82	79	77	83	80	78	76	74		
	横方向 (A)	縦方向 (B)	3.0	90	86	84	81	88	85	83	81	86	84	82	80	84	82	80	79	77		
Hm	1.25Hm	1.25Hm	4.0	91	89	87	85	90	88	86	84	88	86	84	83	86	85	83	82	80		
			5.0	93	90	89	87	91	90	88	86	89	88	86	85	87	86	85	84	81		
			7.0	94	92	91	90	93	91	90	89	91	89	88	87	89	88	87	86	83		
			10.0	95	94	93	92	94	93	92	91	92	91	90	89	90	89	88	88	85		

