

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | XNS 1060 WWK       |           |
| 光源      | LED4000_85_1010 x1 | 1010.0 lm |
| 管理番号    | K0183312 (0) DB 1  |           |
| BZ分類    | BZ1                |           |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |  |     |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|--|-----|
| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |    |    |  |     |
|        | 上方光束    |                 | 0%            | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 0% |  |     |
|        | 下方光束    |                 | 100%          | 壁   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 0% |  |     |
| 室指数    |         |                 | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |  | ZCM |
| 保守率    | 良       | 0.81            | 0.6           | 72  | 63  | 57  | 53  | 71  | 63  | 57  | 53  | 69  | 62  | 57  | 53  | 67  | 61  | 56  | 53 | 52 |    |  |     |
|        | 中       | 0.77            | 0.8           | 81  | 74  | 68  | 65  | 80  | 73  | 68  | 64  | 78  | 72  | 68  | 64  | 76  | 71  | 67  | 64 | 62 |    |  |     |
|        | 否       | 0.68            | 1.0           | 87  | 80  | 76  | 72  | 86  | 80  | 75  | 72  | 84  | 79  | 74  | 71  | 82  | 77  | 74  | 71 | 69 |    |  |     |
|        |         |                 | 1.25          | 92  | 86  | 81  | 78  | 90  | 85  | 81  | 78  | 88  | 84  | 80  | 77  | 86  | 82  | 79  | 77 | 75 |    |  |     |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 94  | 89  | 85  | 82  | 93  | 89  | 85  | 82  | 91  | 87  | 84  | 81  | 89  | 86  | 83  | 81 | 79 |    |  |     |
|        | 等価発光面積  | cm <sup>2</sup> | 2.0           | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 95  | 91  | 89  | 86  | 93  | 90  | 88  | 86 | 84 |    |  |     |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 100 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 92  | 91  | 89 | 87 |    |  |     |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 102 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 92  | 91 | 89 |    |  |     |
| Hm     | 1.30Hm  | 1.30Hm          | 4.0           | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 97  | 95  | 98  | 96  | 95  | 94 | 91 |    |  |     |
|        |         |                 | 5.0           | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 98  | 97  | 95 | 93 |    |  |     |
|        |         |                 | 7.0           | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 97 | 95 |    |  |     |
|        |         |                 | 10.0          | 106 | 105 | 104 | 104 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 99 | 96 |    |  |     |

