

屋内照明器具特性

品番 (品名)	XNS 1 5 6 0 WNK	
光源	LED5000_85_1660 x1	1660.0 lm
管理番号	K0183312 (0) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %		
下方光束	100 %		室指数	照明率 (X0.01)																ZCM		
保守率	良	0.81	0.6	72	63	57	53	71	63	57	53	69	62	57	53	67	61	56	53	52		
	中	0.77	0.8	81	74	68	65	80	73	68	64	78	72	68	64	76	71	67	64	62		
	否	0.68	1.0	87	80	76	72	86	80	75	72	84	79	74	71	82	77	74	71	69		
			1.25	92	86	81	78	90	85	81	78	88	84	80	77	86	82	79	77	75		
下方投影面積	c m ²	等価発光面積	c m ²	1.5	94	89	85	82	93	89	85	82	91	87	84	81	89	86	83	81	79	
				2.0	98	94	91	88	97	93	90	87	95	91	89	86	93	90	88	86	84	
取付高さ	器具間隔最大限		H m	1.30 H m	1.30 H m	2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	92	91	89
	横方向 (A)	縦方向 (B)				3.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	92	91
H m	1.30 H m	1.30 H m	4.0	103	101	99	97	102	100	98	96	100	98	97	95	98	96	95	94	91		
			5.0	104	102	101	99	103	101	100	98	101	99	98	97	99	98	97	95	93		
			7.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95		
			10.0	106	105	104	104	105	104	103	103	103	102	101	101	100	100	99	99	96		

