

屋内照明器具特性

品番 (品名)	P A 4 0 1 5 0 C L N W D 2 3 0									
光源	LED3000_70_1510 x1 1510.0 lm									
管理番号	K0177950(0)DR1									
BZ分類	BZ2									

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	床	10%				10%				10%				10%				0%				
下方光束	100%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	67	58	51	47	66	57	51	47	64	56	51	47	63	55	50	47	45			
	中	0.63	0.8	77	68	62	58	76	68	62	58	74	67	61	58	72	66	61	57	56			
	否	0.56	1.0	83	75	70	65	82	75	69	65	80	73	69	65	78	72	68	65	63			
			1.25	88	81	76	72	87	81	76	72	85	79	75	71	82	78	74	71	69			
下方投影面積			1.5	92	85	81	77	90	85	80	77	88	83	79	76	86	82	78	75	73			
	等価発光面積		2.0	96	91	87	83	95	90	86	83	92	88	85	82	90	87	84	81	79			
取付高さ	器具間隔最大限		2.5	98	94	91	88	97	93	90	87	95	91	89	86	92	90	87	85	83			
		横方向 (A)	縦方向 (B)	3.0	100	97	93	91	99	96	93	90	96	94	91	89	94	92	90	88	86		
1.5m	1.61m	2.16m	4.0	102	99	97	95	101	98	96	94	99	96	95	93	96	95	93	91	89			
2	2.13	2.64	5.0	103	101	99	97	102	100	98	97	100	98	97	95	98	96	95	94	91			
2.5	2.65	3.15	7.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	96	93			
3	3.17	3.68	10.0	106	105	104	103	105	104	103	102	102	102	101	100	100	99	99	98	95			

