

# 屋内照明器具特性

品番 (品名)	NSEK47833J + NEL4605HW														
光源	LED4000_85_6000 x1 6000.0 lm														
管理番号	K0193804(0)DB1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 ( X0.01)																ZCM	
下方光束	100%																			
保守率	良 中 否	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2
		0.77	0.8	6.9	5.8	5.0	4.5	6.7	5.7	5.0	4.4	6.5	5.6	4.9	4.4	6.2	5.4	4.8	4.4	4.2
		0.68	1.0	7.5	6.5	5.8	5.2	7.4	6.4	5.7	5.2	7.1	6.3	5.6	5.2	6.8	6.1	5.6	5.1	4.9
			1.25	8.1	7.2	6.5	6.0	7.9	7.1	6.4	5.9	7.7	6.9	6.3	5.9	7.4	6.8	6.3	5.8	5.6
下方投影面積	c m <sup>2</sup>	1.5	8.5	7.7	7.0	6.5	8.3	7.6	7.0	6.5	8.0	7.4	6.9	6.4	7.8	7.2	6.7	6.4	6.1	
		2.0	9.0	8.4	7.8	7.3	8.9	8.2	7.7	7.3	8.6	8.0	7.6	7.2	8.3	7.9	7.5	7.1	6.9	
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.9	9.2	8.7	8.2	7.8	8.9	8.5	8.1	7.7	8.7	8.3	7.9	7.6	7.4
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.7	8.3	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.1	8.9	8.6	8.3	8.0	7.8
1.5m	1.93m	2.11m	4.0	9.9	9.5	9.2	8.8	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	9.2	9.0	8.7	8.5	8.2
2	2.54	2.66	5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.8	8.6
2.5	3.16	3.22	7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.4	9.2	8.9
3	3.77	3.8	10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

