

屋内照明器具特性

品番 (品名)	NSEK47922J + NEL4503HW	
光源	LED4000_85_4110 x1	4110.0 lm
管理番号	K0193793 (0) DB1	
BZ分類	BZ3	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%																			
下方光束	100%																			
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	63	52	45	40	62	51	45	40	60	50	44	40	58	50	44	40	38
	中	0.77	0.8	73	63	56	52	72	63	56	51	69	61	56	51	67	60	55	51	49
	否	0.68	1.0	80	71	64	59	78	70	64	59	76	69	63	59	73	67	62	59	57
			1.25	85	77	71	67	84	76	71	66	81	75	70	66	79	73	69	66	64
下方投影面積		cm ²	1.5	89	82	76	72	87	81	76	72	85	79	75	71	82	78	74	70	68
等価発光面積		cm ²	2.0	94	88	83	79	92	87	83	79	90	85	81	78	87	83	80	77	75
取付高さ	器具間隔最大限		2.5	97	92	88	84	95	91	87	84	93	89	86	83	90	87	84	82	79
	横方向 (A)	縦方向 (B)	3.0	99	94	91	88	97	93	90	87	95	91	88	86	92	89	87	85	82
1.5m	1.89m	2.09m	4.0	101	98	95	92	100	97	94	92	97	95	92	90	95	93	91	89	86
2	2.5	2.64	5.0	103	100	97	95	101	99	96	94	99	97	95	93	96	95	93	92	89
2.5	3.11	3.21	7.0	104	102	100	99	103	101	99	98	100	99	98	96	98	97	96	95	92
3	3.72	3.8	10.0	105	104	103	101	104	103	102	100	102	101	100	99	100	99	98	97	94

