

屋内照明器具特性

品番 (品名)	XAD5100L				
光源	LLD5000LCC1 ×1 1140.0 1 m				
管理番号	K0187672 (1) DR 1				
BZ分類	BZ3/0.7/BZ2				

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	95 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	62	53	47	42	61	52	47	42	60	52	46	42	58	51	46	42	41	
		0.8	72	64	58	54	71	63	57	53	69	62	57	53	67	61	56	53	51	
		1.0	78	71	65	61	77	70	65	61	75	69	64	61	73	67	63	60	58	
		1.25	83	77	72	68	82	76	71	67	80	74	70	67	78	73	69	67	65	
下方投影面積	c m ²	1.5	86	81	76	72	85	80	75	72	83	78	74	71	81	77	74	71	69	
		2.0	91	86	82	79	89	85	81	78	87	83	80	77	85	82	79	77	75	
取付高さ	器具間隔最大限		2.5	93	89	86	83	92	88	85	82	89	86	84	81	87	85	82	80	78
	横方向 (A)	縦方向 (B)	3.0	95	91	88	86	93	90	88	85	91	88	86	84	89	87	85	83	81
H m	1.24 H m	1.24 H m	4.0	97	94	92	89	96	93	91	89	93	91	89	88	91	89	88	86	84
			5.0	98	96	94	92	97	95	93	91	94	93	91	90	92	91	90	88	86
			7.0	99	98	96	95	98	97	95	94	96	95	93	92	94	93	92	91	88
			10.0	100	99	98	97	99	98	97	96	97	96	95	94	95	94	93	93	90

