

屋内照明器具特性

品番 (品名)	XAD5 160 V	
光源	LLD5010VCC1 ×1	1095.0 l m
管理番号	K0187673 (1) DR 1	
BZ分類	BZ1	

器具効率	96 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	96 %	床		10 %				10 %				10 %				10 %				0 %			
室指数	照明率 (X0.01)																			ZCM			
保守率	良 0.67	0.6	0.6	81	76	72	70	81	75	72	70	79	75	72	69	78	74	71	69	68			
	中 0.63		0.8	86	81	78	75	86	81	78	75	84	80	77	75	83	79	77	75	74			
	否 0.56		1.0	90	85	82	79	89	85	82	79	87	84	81	79	86	83	80	79	77			
下方投影面積	c m ²	等価発光面積	c m ²	1.25	93	88	85	83	92	88	85	83	90	87	84	82	88	86	84	82	80		
				1.5	94	91	88	86	93	90	87	85	92	89	87	85	90	88	86	84	83		
取付高さ	器具間隔最大限		H m	0.81 H m	0.81 H m	2.5	98	96	93	92	97	95	93	91	95	93	92	90	93	92	90	89	87
	横方向 (A)	縦方向 (B)				3.0	99	97	95	93	98	96	94	93	96	94	93	92	94	93	92	91	89
H m	0.81 H m	0.81 H m	4.0	100	99	97	96	99	98	96	95	97	96	95	94	95	94	93	92	90			
			5.0	101	100	98	97	100	99	97	96	98	97	96	95	96	95	94	94	91			
			7.0	102	101	100	99	101	100	99	98	99	98	97	96	97	96	95	95	92			
			10.0	102	102	101	100	101	101	100	99	99	99	98	98	97	97	96	96	93			

