

# 屋内照明器具特性

品番 (品名)	XAD3 1 2 8 V	
光源	LLD3 0 2 0 VCE1 × 1	795.0 1 m
管理番号	K0187666 (1) DR 1	
BZ分類	BZ1	

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %					
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
下方光束	88 %	床		10 %				10 %				10 %				10 %				0 %				
室指数	照明率 ( X 0.01 )																			ZCM				
保守率	良 0.67	0.6	0.6	75	70	66	64	74	69	66	64	73	69	66	64	72	68	66	64	63				
	中 0.63		0.8	80	75	72	70	79	75	72	70	78	74	71	69	77	73	71	69	68				
	否 0.56		1.0	83	79	76	74	82	78	75	73	81	77	75	73	79	77	74	73	72				
下方投影面積	c m <sup>2</sup>	等価発光面積	c m <sup>2</sup>	1.25	85	82	79	77	84	81	79	77	83	80	78	76	82	79	77	76	74			
				1.5	87	84	81	79	86	83	81	79	84	82	80	78	83	81	79	78	76	76		
取付高さ	器具間隔最大限		H m	0.43 H m	H m	0.43 H m	2.5	90	88	86	85	89	87	86	84	88	86	84	83	86	85	83	82	81
	横方向 (A)	縦方向 (B)					3.0	91	89	88	86	90	88	87	86	88	87	86	85	87	86	84	84	82
H m	0.43 H m	0.43 H m	4.0	92	91	89	88	91	90	89	88	89	88	87	86	88	87	86	85	83	83	83	83	
			5.0	93	92	90	89	92	91	90	89	90	89	88	87	88	87	86	85	84	84	84	84	84
			7.0	94	93	92	91	93	92	91	90	91	90	89	89	89	89	88	88	87	85	85	85	85
			10.0	94	93	93	92	93	92	92	91	91	91	90	90	89	89	89	88	86	86	86	86	

