

屋内照明器具特性

品番 (品名)	XAS 5001N	
光源	LLD5000NCC1 ×1 1140.0 lm	
管理番号	K0187899(0)DR1	
BZ分類	BZ2/1.1/BZ1/1.4/BZ2/1.8/BZ1 /3.5/BZ2/8.5/BZ1	

器具効率	76%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	76%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	5.2	4.5	4.0	3.7	5.1	4.5	4.0	3.7	5.0	4.4	4.0	3.7	4.9	4.3	4.0	3.7	3.6
	中	0.63	0.8	6.0	5.4	4.9	4.6	5.9	5.3	4.9	4.6	5.7	5.2	4.9	4.6	5.6	5.1	4.8	4.6	4.4
	否	0.56	1.0	6.5	5.9	5.5	5.2	6.4	5.8	5.5	5.2	6.2	5.8	5.4	5.2	6.0	5.7	5.4	5.1	5.0
			1.25	6.8	6.3	6.0	5.7	6.7	6.3	6.0	5.7	6.6	6.2	5.9	5.6	6.4	6.1	5.8	5.6	5.5
下方投影面積		cm ²	1.5	7.1	6.6	6.3	6.0	7.0	6.6	6.3	6.0	6.8	6.5	6.2	6.0	6.6	6.4	6.1	5.9	5.8
等価発光面積		cm ²	2.0	7.4	7.0	6.7	6.5	7.3	7.0	6.7	6.5	7.1	6.8	6.6	6.4	6.9	6.7	6.5	6.4	6.2
取付高さ	器具間隔最大限		2.5	7.5	7.3	7.0	6.8	7.4	7.2	7.0	6.8	7.3	7.0	6.9	6.7	7.1	6.9	6.8	6.6	6.5
	横方向 (A)	縦方向 (B)	3.0	7.7	7.4	7.2	7.0	7.6	7.3	7.1	7.0	7.4	7.2	7.0	6.9	7.2	7.1	6.9	6.8	6.6
Hm	1.23Hm	1.23Hm	4.0	7.8	7.6	7.4	7.3	7.7	7.5	7.4	7.2	7.5	7.4	7.3	7.1	7.4	7.2	7.1	7.0	6.9
			5.0	7.9	7.7	7.6	7.5	7.8	7.6	7.5	7.4	7.6	7.5	7.4	7.3	7.4	7.4	7.3	7.2	7.0
			7.0	8.0	7.9	7.8	7.7	7.9	7.8	7.7	7.6	7.7	7.6	7.5	7.5	7.5	7.5	7.4	7.3	7.1
			10.0	8.0	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.8	7.7	7.7	7.6	7.6	7.6	7.5	7.5	7.3

