

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB53020                     |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_70_2135 x1 2135.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0189720(0)DB1               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ6                          |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                   |         |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|--------|-------------------|---------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 器具効率   | 100%              | 天井      | 80%              |      |      |      | 70%  |      |      |      | 50%  |      |      |      | 30%  |      |      |      | 0%   |      |    |
|        | 上方光束              |         | 16%              | 反射率  | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 0% |
|        | 下方光束              |         | 84%              |      | 床    | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |    |
| 室指数    | 照明率 ( X0.01 ) ZCM |         |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 保守率    | 良                 | 0.63    | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |
|        | 中                 | 0.6     | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |
|        | 否                 | 0.56    | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |
|        | 0.56              | 0.56    | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |
| 下方投影面積 | c m <sup>2</sup>  |         | 1.25             | 1.5  | 2.0  | 2.5  | 3.0  | 3.5  | 4.0  | 4.5  | 5.0  | 5.5  | 6.0  | 6.5  | 7.0  | 7.5  | 8.0  | 8.5  | 9.0  | 9.5  |    |
|        | 等価発光面積            |         | c m <sup>2</sup> |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 取付高さ   | 器具間隔最大限           |         |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|        | 横方向 (A)           | 縦方向 (B) |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 1.5m   | 2.03m             | 2.03m   | 4.0              | 5.0  | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 11.0 | 12.0 | 13.0 | 14.0 | 15.0 | 16.0 | 17.0 | 18.0 | 19.0 | 20.0 | 21.0 |    |
| 2      | 2.68              | 2.68    | 5.0              | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 11.0 | 12.0 | 13.0 | 14.0 | 15.0 | 16.0 | 17.0 | 18.0 | 19.0 | 20.0 | 21.0 | 22.0 |    |
| 2.5    | 3.35              | 3.35    | 6.0              | 7.0  | 8.0  | 9.0  | 10.0 | 11.0 | 12.0 | 13.0 | 14.0 | 15.0 | 16.0 | 17.0 | 18.0 | 19.0 | 20.0 | 21.0 | 22.0 | 23.0 |    |
| 3      | 4.02              | 4.02    | 7.0              | 8.0  | 9.0  | 10.0 | 11.0 | 12.0 | 13.0 | 14.0 | 15.0 | 16.0 | 17.0 | 18.0 | 19.0 | 20.0 | 21.0 | 22.0 | 23.0 | 24.0 |    |

