

屋内照明器具特性

品番 (品名)	XAS 5 5 0 1 L				
光源	LLD5000LCC1 ×1 1140.0 1 m				
管理番号	K0187899 (0) DR 1				
B Z 分類	BZ2 / 1.1 / BZ1 / 1.4 / BZ2 / 1.8 / BZ1 / 3.5 / BZ2 / 8.5 / BZ1				

器具効率	76 %	天井	80 %				70 %				50 %				30 %				0 %			
	上方光束		0 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
	下方光束		76 %		床	10 %				10 %				10 %				10 %				0 %
室指数		照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	5.2	4.5	4.0	3.7	5.1	4.5	4.0	3.7	5.0	4.4	4.0	3.7	4.9	4.3	4.0	3.7	3.6		
	中	0.63	0.8	6.0	5.4	4.9	4.6	5.9	5.3	4.9	4.6	5.7	5.2	4.9	4.6	5.6	5.1	4.8	4.6	4.4		
	否	0.56	1.0	6.5	5.9	5.5	5.2	6.4	5.8	5.5	5.2	6.2	5.8	5.4	5.2	6.0	5.7	5.4	5.1	5.0		
			1.25	6.8	6.3	6.0	5.7	6.7	6.3	6.0	5.7	6.6	6.2	5.9	5.6	6.4	6.1	5.8	5.6	5.5		
下方投影面積			1.5	7.1	6.6	6.3	6.0	7.0	6.6	6.3	6.0	6.8	6.5	6.2	6.0	6.6	6.4	6.1	5.9	5.8		
			2.0	7.4	7.0	6.7	6.5	7.3	7.0	6.7	6.5	7.1	6.8	6.6	6.4	6.9	6.7	6.5	6.4	6.2		
取付高さ	器具間隔最大限		2.5	7.5	7.3	7.0	6.8	7.4	7.2	7.0	6.8	7.3	7.0	6.9	6.7	7.1	6.9	6.8	6.6	6.5		
	横方向 (A)	縦方向 (B)	3.0	7.7	7.4	7.2	7.0	7.6	7.3	7.1	7.0	7.4	7.2	7.0	6.9	7.2	7.1	6.9	6.8	6.6		
H m	1.23 H m	1.23 H m	4.0	7.8	7.6	7.4	7.3	7.7	7.5	7.4	7.2	7.5	7.4	7.3	7.1	7.4	7.2	7.1	7.0	6.9		
			5.0	7.9	7.7	7.6	7.5	7.8	7.6	7.5	7.4	7.6	7.5	7.4	7.3	7.4	7.4	7.3	7.2	7.0		
			7.0	8.0	7.9	7.8	7.7	7.9	7.8	7.7	7.6	7.7	7.6	7.5	7.5	7.5	7.5	7.4	7.3	7.1		
			10.0	8.0	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.8	7.7	7.7	7.6	7.6	7.6	7.5	7.5	7.3		

