

# 屋内照明器具特性

|         |                |           |
|---------|----------------|-----------|
| 品番 (品名) | XAS5521L       |           |
| 光源      | LLD5020LCC1 ×1 | 1085.0 1m |
| 管理番号    | K0187901(0)DR1 |           |
| BZ分類    | BZ1            |           |

|                |                    |                    |             |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|----------------|--------------------|--------------------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率           | 78%                | 天井                 | 80%         |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|                | 上方光束               |                    | 0%          | 70 | 50 | 30 | 10  | 70 | 50 | 30 | 10  | 70 | 50 | 30 | 10  | 70 | 50 | 30 | 10  | 0% |
| 下方光束           | 78%                | 床                  | 10%         |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 室指数            |                    |                    | 照明率 (×0.01) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率            | 良                  | 0.67               | 0.6         | 64 | 59 | 56 | 54  | 64 | 59 | 56 | 54  | 63 | 58 | 56 | 53  | 62 | 58 | 55 | 53  | 53 |
|                | 中                  | 0.63               | 0.8         | 69 | 65 | 62 | 60  | 69 | 64 | 62 | 59  | 67 | 64 | 61 | 59  | 66 | 63 | 61 | 59  | 58 |
|                | 否                  | 0.56               | 1.0         | 72 | 68 | 66 | 63  | 72 | 68 | 65 | 63  | 70 | 67 | 65 | 63  | 69 | 66 | 64 | 63  | 62 |
| 下方投影面積         | 等価発光面積             | cm <sup>2</sup>    | 1.25        | 75 | 71 | 69 | 67  | 74 | 71 | 68 | 67  | 73 | 70 | 68 | 66  | 71 | 69 | 67 | 66  | 65 |
|                |                    |                    | 1.5         | 77 | 74 | 71 | 69  | 76 | 73 | 71 | 69  | 74 | 72 | 70 | 68  | 73 | 71 | 69 | 68  | 67 |
| 取付高さ           | 器具間隔最大限            |                    | 2.5         | 80 | 78 | 76 | 75  | 79 | 77 | 76 | 74  | 78 | 76 | 75 | 73  | 76 | 75 | 74 | 73  | 71 |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0         | 81 | 79 | 77 | 76  | 80 | 78 | 77 | 76  | 78 | 77 | 76 | 75  | 77 | 76 | 75 | 74  | 72 |
| H <sub>m</sub> | 0.44H <sub>m</sub> | 0.44H <sub>m</sub> | 4.0         | 82 | 80 | 79 | 78  | 81 | 80 | 78 | 77  | 79 | 78 | 77 | 76  | 78 | 77 | 76 | 75  | 74 |
|                |                    |                    | 5.0         | 82 | 81 | 80 | 79  | 82 | 80 | 80 | 79  | 80 | 79 | 78 | 77  | 78 | 78 | 77 | 76  | 74 |
|                |                    |                    | 7.0         | 83 | 82 | 81 | 81  | 82 | 81 | 81 | 80  | 81 | 80 | 79 | 79  | 79 | 78 | 78 | 77  | 75 |
|                |                    |                    | 10.0        | 84 | 83 | 82 | 82  | 83 | 82 | 82 | 81  | 81 | 81 | 80 | 80  | 79 | 79 | 79 | 78  | 76 |

