

屋内照明器具特性

品番 (品名)	LGB57641														
光源	LDG3L/F8/C/B2 x6 300.0 1m														
管理番号	K0189936(1)DR1														
BZ分類	BZ7/1.1/BZ6/3.5/BZ7/4.5/BZ6/6.0/BZ7														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	36%	室指数	照明率 (X0.01)																ZCM		
下方光束	64%																				
保守率	良 中 否	0.69	0.6	48	35	27	21	44	33	26	20	38	29	23	18	33	25	20	16	12	
		0.67	0.8	56	44	36	30	53	41	34	28	46	37	30	25	39	32	27	23	17	
			1.0	62	51	42	36	58	48	40	34	51	42	36	31	43	37	31	27	21	
		0.63	1.25	68	57	49	43	64	54	46	41	55	47	41	36	48	41	37	32	25	
下方投影面積	c m ²	1.5	72	62	54	48	68	58	51	46	59	52	46	41	51	45	40	36	28		
		2.0	78	69	62	56	73	65	59	53	64	58	52	48	55	50	46	42	34		
取付高さ	器具間隔最大限		2.5	81	74	67	62	77	70	64	59	67	62	57	53	58	54	50	47	37	
	横方向 (A)	縦方向 (B)		3.0	84	77	71	66	79	73	67	63	70	65	60	56	61	57	53	50	40
1.5m	1.42m	1.34m	4.0	88	82	77	72	82	77	73	69	73	69	65	62	64	60	57	55	44	
2	1.79	1.72	5.0	90	85	80	76	85	80	76	73	75	71	68	65	66	63	60	58	47	
2.5	2.16	2.13	7.0	92	88	85	82	87	84	81	78	77	75	72	70	68	66	64	62	50	
3	2.55	2.55	10.0	94	91	89	86	89	87	84	82	80	77	75	73	70	69	67	65	53	

