

# 屋内照明器具特性

品番 (品名)	LGB50416K														
光源	LED3500_70_300 x1 300.0 l m														
管理番号	K0153783(0)DB1														
BZ分類	BZ7														

器具効率	101%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	16%	室指数																		
下方光束	85%	照明率 ( X0.01) ZCM																		
保守率	良 0.69 中 0.67 否 0.63	0.6	50	37	28	22	48	35	27	22	43	33	26	21	40	30	24	19	16	
		0.8	59	46	37	30	56	44	36	30	51	41	34	28	47	38	32	27	23	
		1.0	65	53	43	37	62	51	42	36	57	47	40	34	52	44	37	32	28	
		1.25	71	59	50	43	68	57	49	42	62	53	46	40	57	49	43	38	33	
下方投影面積	c m <sup>2</sup>	1.5	75	64	56	49	72	62	54	47	66	57	51	45	60	53	47	43	37	
		2.0	81	71	64	57	78	69	62	56	71	64	58	53	65	59	54	50	44	
取付高さ	器具間隔最大限		2.5	85	76	69	63	82	74	67	61	75	69	63	58	64	59	55	49	
	横方向 (A)	縦方向 (B)	3.0	88	80	74	68	84	77	71	66	78	72	67	62	72	67	63	59	53
1.5m	1.95 m	1.99 m	4.0	92	85	80	74	88	82	77	72	82	77	72	68	76	72	68	65	58
2	2.59	2.62	5.0	94	89	84	79	91	86	81	77	84	80	76	73	78	75	71	69	62
2.5	3.25	3.26	7.0	97	93	89	85	94	90	86	83	87	84	81	78	81	79	76	74	66
3	3.88	3.88	10.0	99	96	93	90	96	93	90	87	90	87	85	83	84	82	80	78	70

