

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XND1007BWK                  |
| 光源       | LED4000_85_950 x1 950.0 l m |
| 管理番号     | K0176489(0)DB1              |
| BZ分類     | BZ1                         |

|        |                  |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%             | 天井       | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |    |
|        | 上方光束             |          | 0%               | 壁   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
|        | 下方光束             |          | 100%             |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    |
| 室指数    | 照明率 ( X0.01 )    |          |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良                | 0.81     | 0.6              | 74  | 66  | 61  | 57  | 73  | 66  | 61  | 57  | 72  | 65  | 60  | 57  | 70  | 64  | 60  | 57  | 55  |    |
|        | 中                | 0.77     | 0.8              | 83  | 76  | 71  | 68  | 82  | 76  | 71  | 68  | 81  | 75  | 71  | 68  | 79  | 74  | 70  | 67  | 66  |    |
|        | 否                | 0.68     | 1.0              | 89  | 83  | 78  | 75  | 88  | 82  | 78  | 75  | 86  | 81  | 77  | 74  | 84  | 80  | 77  | 74  | 72  |    |
|        |                  |          | 1.25             | 93  | 88  | 84  | 81  | 92  | 87  | 83  | 80  | 90  | 86  | 82  | 80  | 88  | 85  | 82  | 79  | 78  |    |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 96  | 91  | 87  | 84  | 95  | 90  | 87  | 84  | 93  | 89  | 86  | 83  | 91  | 88  | 85  | 83  | 81  |    |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0 | 99  | 95  | 92  | 90  | 98  | 94  | 92  | 89  | 96  | 93  | 90  | 88  | 94  | 91  | 89  | 87  | 86 |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 101 | 98  | 95  | 93  | 100 | 97  | 95  | 92  | 98  | 95  | 93  | 91  | 96  | 94  | 92  | 90  | 88  |    |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 102 | 100 | 97  | 95  | 101 | 99  | 96  | 95  | 99  | 97  | 95  | 93  | 97  | 95  | 94  | 92  | 90  |    |
| H m    | 1.17 H m         | 1.17 H m | 4.0              | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 98  | 101 | 99  | 97  | 96  | 98  | 97  | 96  | 95  | 93  |    |
|        |                  |          | 5.0              | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 99  | 101 | 100 | 99  | 98  | 99  | 98  | 97  | 96  | 94  |    |
|        |                  |          | 7.0              | 106 | 105 | 103 | 102 | 105 | 104 | 102 | 101 | 102 | 102 | 101 | 100 | 100 | 100 | 99  | 98  | 96  |    |
|        |                  |          | 10.0             | 107 | 106 | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 97  |    |

