

# 屋内照明器具特性

|         |                   |  |  |  |  |          |  |  |  |  |
|---------|-------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | XND1007SFK        |  |  |  |  |          |  |  |  |  |
| 光源      | LED2700_85_720 x1 |  |  |  |  | 720.0 lm |  |  |  |  |
| 管理番号    | K0176491(0)DB1    |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ1               |  |  |  |  |          |  |  |  |  |

|        |               |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
|--------|---------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|
| 器具効率   | 100%          | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |     |    |
|        | 上方光束          |         | 0%   | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 0% |
|        | 下方光束          |         | 100% |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |     |    |
| 室指数    | 照明率 ( X0.01 ) |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |    |
| 保守率    | 良             | 0.81    | 0.6  | 74  | 66  | 60  | 57  | 73  | 65  | 60  | 57  | 71  | 64  | 60  | 56  | 70  | 64  | 59  | 56 | 55  |    |
|        | 中             | 0.77    | 0.8  | 83  | 76  | 71  | 67  | 82  | 75  | 71  | 67  | 80  | 74  | 70  | 67  | 79  | 74  | 70  | 67 | 65  |    |
|        | 否             | 0.68    | 1.0  | 89  | 82  | 78  | 74  | 88  | 82  | 78  | 74  | 86  | 81  | 77  | 74  | 84  | 80  | 76  | 74 | 72  |    |
|        |               |         | 1.25 | 93  | 87  | 83  | 80  | 92  | 87  | 83  | 80  | 90  | 86  | 82  | 79  | 88  | 84  | 81  | 79 | 77  |    |
| 下方投影面積 |               |         | 1.5  | 96  | 91  | 87  | 84  | 94  | 90  | 87  | 84  | 92  | 89  | 86  | 83  | 90  | 87  | 85  | 82 | 81  |    |
|        |               |         | 2.0  | 99  | 95  | 92  | 89  | 98  | 94  | 91  | 89  | 96  | 93  | 90  | 88  | 94  | 91  | 89  | 87 | 85  |    |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 101 | 98  | 95  | 93  | 100 | 97  | 94  | 92  | 98  | 95  | 93  | 91  | 96  | 94  | 92  | 90 | 88  |    |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 102 | 99  | 97  | 95  | 101 | 99  | 96  | 94  | 99  | 97  | 95  | 93  | 97  | 95  | 94  | 92 | 90  |    |
| Hm     | 1.17Hm        | 1.17Hm  | 4.0  | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 97  | 100 | 99  | 97  | 96  | 98  | 97  | 96  | 95 | 92  |    |
|        |               |         | 5.0  | 105 | 103 | 101 | 100 | 104 | 102 | 101 | 99  | 101 | 100 | 99  | 98  | 99  | 98  | 97  | 96 | 94  |    |
|        |               |         | 7.0  | 106 | 105 | 103 | 102 | 105 | 104 | 102 | 101 | 102 | 101 | 101 | 100 | 100 | 100 | 99  | 98 | 96  |    |
|        |               |         | 10.0 | 107 | 106 | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 99 | 97  |    |

