

屋内照明器具特性

品番 (品名)	LGB15452K														
光源	LDA4L-H-E17/S/4 x1 440.0lm														
管理番号	K0170957(0)DR1														
BZ分類	BZ6/0.7/BZ5/1.1/BZ6														

器具効率	98%	天井	80%				70%				50%				30%				0%		
	上方光束		26%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		72%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良 中 否	0.67	0.6	50	39	31	26	48	37	30	25	43	34	28	23	39	31	26	22	18	
		0.63	0.8	59	48	40	34	56	46	39	33	50	42	36	31	45	38	33	29	25	
		0.56	1.0	65	54	46	41	62	52	45	39	55	47	41	37	50	43	38	34	29	
			1.25	71	60	53	47	67	58	51	45	60	53	47	42	54	48	43	39	33	
下方投影面積	等価発光面積	c m ²	1.5	74	65	58	52	71	62	55	50	63	57	51	47	57	51	47	43	37	
			2.0	80	71	65	59	76	68	62	57	68	62	57	53	61	57	53	49	42	
取付高さ	器具間隔最大限		2.5	83	76	70	65	79	72	67	62	71	66	62	58	64	60	56	53	46	
	横方向 (A)	縦方向 (B)	3.0	85	79	73	69	81	76	71	66	74	69	65	61	66	63	59	56	48	
H _m	1.34H _m	1.34H _m	4.0	88	83	79	74	84	80	75	72	77	73	69	66	69	66	63	61	52	
			5.0	90	86	82	78	86	82	79	75	79	75	72	69	71	69	66	64	55	
			7.0	93	89	86	83	89	86	83	80	81	78	76	74	74	72	70	68	59	
			10.0	95	92	90	87	91	88	86	84	83	81	79	77	76	74	73	71	62	

