

# 屋内照明器具特性

品番 (品名)	LGB58077F				
光源	LDA4L-H-E17/S/4 x1 440.0lm				
管理番号	K0123436(0)DB1				
BZ分類	BZ4/0.7/BZ3				

器具効率	71%	天井	80%				70%				50%				30%				0%		
	上方光束		1%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		70%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	43	35	30	27	42	35	30	27	41	34	30	26	39	33	29	26	25	
	中	0.63	0.8	51	44	39	35	50	43	39	35	48	42	38	35	46	41	38	35	33	
	否	0.56	1.0	56	49	45	41	55	49	44	41	53	48	44	41	51	46	43	40	39	
			1.25	60	54	50	46	59	53	49	46	57	52	49	46	55	51	48	45	44	
下方投影面積			1.5	63	57	53	50	61	57	53	50	59	55	52	49	57	54	51	49	47	
			2.0	66	62	58	55	65	61	58	55	63	59	57	54	61	58	56	54	52	
取付高さ	器具間隔最大限		2.5	68	65	61	59	67	64	61	58	65	62	60	58	63	61	59	57	55	
	横方向 (A)	縦方向 (B)	3.0	70	66	64	61	69	66	63	61	66	64	62	60	64	62	61	59	57	
Hm	1.39Hm	1.39Hm	4.0	71	69	67	65	70	68	66	64	68	66	65	63	66	65	63	62	60	
			5.0	73	70	69	67	71	70	68	66	69	68	66	65	68	66	65	64	62	
			7.0	74	72	71	70	73	71	70	69	71	70	68	67	69	68	67	66	64	
			10.0	75	74	73	72	74	73	72	71	72	71	70	69	70	69	69	68	66	

