

屋内照明器具特性	
品番 (品名)	LGW85014SF
光源	LDA4L-H-E17/S/4 ×1 440.0 lm
管理番号	K0126055(1)DB1
BZ分類	BZ8/4.5/BZ7/8.5/BZ8

器具効率	70%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	27%	床	10%				10%				10%				10%				0%	
下方光束	43%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.2	2.3	1.7	1.3	2.9	2.1	1.6	1.2	2.5	1.8	1.4	1.1	2.1	1.6	1.2	9	6
	中	0.6	0.8	3.8	2.9	2.3	1.9	3.5	2.7	2.2	1.8	3.0	2.3	1.9	1.5	2.5	2.0	1.6	13	9
	否	0.56	1.0	4.2	3.4	2.8	2.3	3.9	3.1	2.6	2.2	3.3	2.7	2.3	1.9	2.8	2.3	1.9	16	12
			1.25	4.6	3.8	3.2	2.7	4.3	3.6	3.0	2.6	3.6	3.1	2.6	2.3	3.1	2.6	2.3	20	14
下方投影面積		cm ²	1.5	4.9	4.2	3.6	3.1	4.5	3.9	3.4	2.9	3.9	3.4	2.9	2.6	3.3	2.9	2.5	2.2	1.6
等価発光面積		cm ²	2.0	5.3	4.7	4.1	3.7	4.9	4.4	3.9	3.5	4.2	3.8	3.4	3.1	3.6	3.2	2.9	2.7	2.0
取付高さ	器具間隔最大限		2.5	5.6	5.0	4.5	4.1	5.2	4.7	4.2	3.9	4.5	4.1	3.7	3.4	3.8	3.5	3.2	3.0	2.2
	横方向 (A)	縦方向 (B)	3.0	5.8	5.2	4.8	4.4	5.4	4.9	4.5	4.2	4.7	4.3	4.0	3.7	4.0	3.7	3.4	3.2	2.4
Hm	1.91Hm	1.91Hm	4.0	6.0	5.6	5.2	4.9	5.6	5.2	4.9	4.6	4.9	4.6	4.3	4.0	4.2	4.0	3.7	3.5	2.7
			5.0	6.2	5.8	5.5	5.2	5.8	5.5	5.2	4.9	5.0	4.8	4.5	4.3	4.3	4.1	3.9	3.8	2.9
			7.0	6.4	6.1	5.8	5.6	6.0	5.7	5.5	5.2	5.2	5.0	4.8	4.6	4.5	4.4	4.2	4.1	3.2
			10.0	6.5	6.3	6.1	5.9	6.1	5.9	5.8	5.6	5.4	5.2	5.1	4.9	4.7	4.6	4.4	4.3	3.4

