

# 屋内照明器具特性

品番 (品名)	XND1006SVK	
光源	LED3500_85_955 ×1	955.0 lm
管理番号	K0176481(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.81	0.6	79	72	67	64	78	72	67	64	77	71	67	64	75	70	67	64	63
	中	0.77	0.8	87	81	76	73	86	80	76	73	84	79	75	73	83	78	75	73	71
	否	0.68	1.0	91	86	82	79	90	85	81	79	89	84	81	78	87	83	80	78	76
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	95	90	87	84	94	89	86	83	92	88	85	83	90	87	85	82	81
			1.5	97	93	90	87	96	92	89	87	94	91	88	86	92	90	87	86	84
取付高さ	器具間隔最大限		2.5	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90
	横方向 (A)	縦方向 (B)	3.0	103	101	98	97	102	100	98	96	100	98	96	95	98	96	95	94	92
Hm	0.74Hm	0.74Hm	4.0	104	103	101	99	103	102	100	99	101	100	98	97	99	98	97	96	94
			5.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	96	
			10.0	107	106	105	105	106	105	104	104	103	102	102	101	101	100	100	97	

