

屋内照明器具特性

品番 (品名)	SLB80516																
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 1 m																
管理番号	K0192638(0)DB1																
BZ分類	BZ3/0.9/BZ2																

器具効率	28%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	6%	床	10%				10%				10%				10%				0%	
下方光束	22%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.67	0.6	17	14	12	10	16	13	11	10	15	12	11	10	14	12	10	9	8
	中	0.63	0.8	19	17	15	14	19	16	15	13	17	15	14	13	16	14	13	12	11
	否	0.56	1.0	21	19	17	16	21	18	17	16	19	17	16	15	18	16	15	14	13
			1.25	23	21	19	18	22	20	19	18	20	19	18	17	19	18	17	16	15
下方投影面積		cm ²	1.5	24	22	21	19	23	21	20	19	21	20	19	18	20	19	18	17	16
等価発光面積		cm ²	2.0	25	24	22	21	24	23	22	21	23	22	21	20	21	20	19	19	17
取付高さ	器具間隔最大限		2.5	26	25	24	23	25	24	23	22	23	22	22	21	22	21	20	20	18
	横方向 (A)	縦方向 (B)	3.0	27	25	24	24	26	25	24	23	24	23	22	22	22	21	21	20	19
H _m	1.42H _m	1.48H _m	4.0	27	26	26	25	26	25	25	24	24	24	23	23	23	22	22	21	19
			5.0	28	27	26	26	27	26	25	25	25	24	24	23	23	23	22	22	20
			7.0	28	28	27	27	27	27	26	26	25	25	24	24	23	23	23	23	20
			10.0	28	28	28	27	27	27	27	26	25	25	25	24	23	23	23	23	21

