

屋内照明器具特性

品番 (品名)	SLB80526															
光源	LDA4L-H-E17/S/4 x1 440.0lm															
管理番号	K0192672(0)DB1															
BZ分類	BZ8/0.7/BZ7/0.9/BZ6/1.4/BZ5															

器具効率	10%	天井	80%				70%				50%				30%				0%	
	上方光束		1%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	9%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	4	3	2	1	4	3	2	1	4	3	2	1	3	2	2	1	1
	中	0.63	0.8	5	4	3	3	5	4	3	3	5	4	3	2	5	4	3	2	2
	否	0.56	1.0	6	5	4	3	6	5	4	3	6	5	4	3	5	4	4	3	3
下方投影面積		cm ²	1.25	7	6	5	4	7	6	5	4	6	5	5	4	6	5	5	4	4
	等価発光面積	cm ²	1.5	7	6	6	5	7	6	6	5	7	6	5	5	6	6	5	5	5
取付高さ	器具間隔最大限		2.5	8	8	7	7	8	8	7	7	8	7	7	7	8	7	7	6	6
	横方向 (A)	縦方向 (B)	3.0	9	8	8	7	8	8	8	7	8	8	7	7	8	7	7	6	6
Hm	0.00Hm	0.20Hm	4.0	9	9	8	8	9	8	8	8	8	8	8	8	8	8	8	7	7
			5.0	9	9	9	8	9	9	8	8	9	8	8	8	8	8	8	8	7
			7.0	9	9	9	9	9	9	9	9	9	9	9	8	9	8	8	8	8
			10.0	10	9	9	9	9	9	9	9	9	9	9	9	9	9	9	8	8

