

屋内照明器具特性

品番 (品名)	XND2008WNK			
光源	LED5000_85_2050 ×1 2050.0 lm			
管理番号	K0176484(0)DB1			
BZ分類	BZ1			

器具効率	101%	天井	80%				70%				50%				30%				0%		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30		10	
																					床
上方光束	0%	室指数	照明率 (X 0.01)																		
下方光束	101%	保守率																			
良	0.81	0.6	77	70	65	61	76	69	64	61	75	68	64	61	73	68	64	61	60		
中	0.77	0.8	85	78	74	70	84	78	73	70	82	77	73	70	81	76	72	70	68		
否	0.68	1.0	90	84	80	76	89	83	79	76	87	82	79	76	85	81	78	75	74		
下方投影面積 等価発光面積	cm ²	1.25	94	89	85	82	93	88	84	81	91	87	84	81	89	86	83	80	79		
		1.5	97	92	88	85	96	91	88	85	93	90	87	84	92	88	86	84	82		
取得 高さ	器具間隔最大限		2.5																		
	横方向 (A)	縦方向 (B)																			
Hm	0.74 Hm	0.74 Hm	4.0	105	102	101	99	103	101	100	98	101	100	98	97	99	98	97	96	93	
			5.0	105	104	102	110	104	103	111	100	102	110	100	98	100	99	98	97	95	
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96	
			10.0	107	106	105	105	106	105	104	104	103	103	102	102	101	101	100	97		

