

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | XND2506BWK         |           |
| 光源      | LED4000_85_2335 ×1 | 2335.0 lm |
| 管理番号    | K0176482(0)DB1     |           |
| BZ分類    | BZ1                |           |

|        |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        | 上方光束<br>0%      |         | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 下方光束   | 100%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |
| 保守率    | 良 0.81          | 0.6     | 80   | 72  | 68  | 65  | 79  | 72  | 68  | 65  | 77  | 71  | 67  | 64  | 76  | 71  | 67  | 64  | 63  |     |
|        | 中 0.77          |         | 0.8  | 87  | 81  | 77  | 74  | 86  | 80  | 76  | 73  | 85  | 80  | 76  | 73  | 83  | 79  | 75  | 73  | 72  |
|        | 否 0.68          |         | 1.0  | 92  | 86  | 82  | 79  | 91  | 86  | 82  | 79  | 89  | 84  | 81  | 79  | 87  | 83  | 81  | 78  | 77  |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 95   | 90  | 87  | 84  | 94  | 90  | 86  | 84  | 92  | 89  | 86  | 83  | 91  | 87  | 85  | 83  | 81  |     |
|        |                 | 1.5     | 98   | 93  | 90  | 87  | 97  | 93  | 90  | 87  | 95  | 91  | 89  | 86  | 93  | 90  | 88  | 86  | 84  |     |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 100  | 97  | 94  | 92  | 99  | 96  | 94  | 92  | 97  | 95  | 93  | 91  | 95  | 93  | 91  | 90  | 88  |     |
|        |                 | 2.5     | 102  | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 99  | 97  | 95  | 93  | 97  | 95  | 94  | 92  | 90  |     |
| 取付高さ   | 器具間隔最大限         |         | 3.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94  | 92  |
|        | 横方向 (A)         | 縦方向 (B) | 4.0  | 105 | 103 | 101 | 100 | 104 | 102 | 100 | 99  | 101 | 100 | 99  | 97  | 99  | 98  | 97  | 96  | 94  |
| Hm     | 0.74Hm          | 0.74Hm  | 5.0  | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 97  | 95  |
|        |                 |         | 7.0  | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 100 | 99  | 99  | 96  |
|        |                 |         | 10.0 | 107 | 106 | 105 | 105 | 106 | 105 | 104 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 97  |

