

屋内照明器具特性

品番 (品名)	XLGEC519HU																
光源	LDA4L-H-E17/S/4 x1 440.0lm																
管理番号	K0125088(1)DB1																
BZ分類	BZ10																

器具効率	57%	天井	80%				70%				50%				30%				0%		
	上方光束 30%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				下方光束 27%	10%				10%				10%				10%				0%
室指数	照明率 (X0.01) ZCM																				
保守率	良 0.63	0.6	0.6	2.4	1.6	1.2	0.9	2.1	1.5	1.1	0.8	1.7	1.2	0.8	0.6	1.3	0.9	0.6	0.4	0.1	
	中 0.6	0.8	2.8	2.1	1.6	1.2	2.5	1.9	1.4	1.1	2.0	1.5	1.2	0.9	1.6	1.2	0.9	0.6	0.2		
	否 0.56	1.0	3.1	2.4	1.9	1.5	2.8	2.2	1.8	1.4	2.3	1.8	1.4	1.1	1.7	1.4	1.1	0.8	0.4		
	下方投影面積	cm ²	1.25	3.5	2.8	2.3	1.9	3.1	2.5	2.1	1.7	2.5	2.0	1.7	1.4	1.9	1.6	1.3	1.1	0.5	
等価発光面積	cm ²		1.5	3.7	3.1	2.6	2.2	3.3	2.8	2.3	2.0	2.7	2.2	1.9	1.6	2.1	1.7	1.5	1.2	0.6	
取付高さ	器具間隔最大限		2.5	4.2	3.7	3.3	3.0	3.9	3.4	3.0	2.7	3.1	2.8	2.5	2.2	2.5	2.2	2.0	1.8	1.0	
	横方向 (A)	縦方向 (B)	3.0	4.4	3.9	3.5	3.2	4.0	3.6	3.3	2.9	3.3	3.0	2.7	2.4	2.6	2.3	2.1	1.9	1.2	
Hm	0.00Hm	0.00Hm	4.0	4.6	4.2	3.9	3.6	4.2	3.9	3.6	3.3	3.5	3.2	3.0	2.7	2.8	2.6	2.4	2.2	1.4	
			5.0	4.7	4.4	4.1	3.8	4.3	4.1	3.8	3.5	3.6	3.4	3.1	3.0	2.9	2.7	2.5	2.4	1.5	
			7.0	4.9	4.6	4.4	4.2	4.5	4.3	4.1	3.9	3.8	3.6	3.4	3.2	3.0	2.9	2.8	2.6	1.7	
			10.0	5.0	4.8	4.7	4.5	4.7	4.5	4.3	4.1	3.9	3.7	3.6	3.5	3.2	3.1	3.0	2.8	1.9	

