

屋内照明器具特性	
品番 (品名)	LGB19225WF
光源	LDA7L-D-G/S/Z6 ×2 810.0 lm
管理番号	K0189054(1)DR1
BZ分類	BZ10/0.7/BZ9

器具効率	84%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	39%	室指数	床	10%				10%				10%				10%				0%	
下方光束	45%		照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6 中 否 0.56	0.6	3.7	2.6	1.9	1.4	3.3	2.4	1.7	1.3	2.8	2.0	1.5	1.1	2.2	1.6	1.2	0.9	0.4	
	0.8		4.4	3.3	2.6	2.0	4.0	3.0	2.4	1.9	3.3	2.5	2.0	1.6	2.7	2.1	1.6	1.3	0.7		
	1.0		4.9	3.8	3.1	2.5	4.4	3.5	2.8	2.3	3.7	2.9	2.4	2.0	3.0	2.4	2.0	1.6	1.0		
	1.25		5.3	4.3	3.6	3.0	4.9	4.0	3.3	2.8	4.0	3.4	2.8	2.4	3.3	2.8	2.3	2.0	1.2		
下方投影面積	cm ²	等価発光面積	cm ²	1.5	5.7	4.8	4.0	3.5	5.2	4.4	3.7	3.2	4.3	3.7	3.2	2.7	3.5	3.0	2.6	2.3	1.5
				2.0	6.2	5.3	4.7	4.1	5.7	4.9	4.4	3.9	4.7	4.2	3.7	3.3	3.9	3.4	3.1	2.7	1.8
取付高さ	器具間隔最大限		Hm	2.5	6.5	5.8	5.2	4.6	6.0	5.3	4.8	4.3	5.0	4.5	4.1	3.7	4.1	3.7	3.4	3.1	2.1
	横方向 (A)	縦方向 (B)		3.0	6.7	6.1	5.5	5.0	6.2	5.6	5.1	4.7	5.2	4.8	4.4	4.0	4.3	4.0	3.7	3.4	2.3
Hm	2.37Hm	2.37Hm	4.0	7.0	6.5	6.0	5.6	6.5	6.0	5.6	5.2	5.5	5.1	4.8	4.5	4.6	4.3	4.0	3.8	2.7	
			5.0	7.2	6.7	6.3	5.9	6.7	6.3	5.9	5.6	5.7	5.4	5.1	4.8	4.8	4.5	4.3	4.0	2.9	
			7.0	7.5	7.1	6.7	6.4	6.9	6.6	6.3	6.0	5.9	5.7	5.4	5.2	5.0	4.8	4.6	4.4	3.2	
			10.0	7.7	7.4	7.1	6.9	7.1	6.9	6.6	6.4	6.1	5.9	5.7	5.6	5.2	5.0	4.9	4.7	3.5	

