

# 屋内照明器具特性

品番 (品名)	LGB81649	
光源	LDA4 WW- H- E17 / S / 4 ×1	440.0 lm
管理番号	K0187732 ( 0 ) DB 1	
BZ分類	BZ5 / 1.1 / BZ4	

器具効率	61%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 61%	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																ZCM			
保守率	良 0.67	0.6	34	27	22	18	33	26	22	18	32	26	21	18	31	25	21	18	17	
	中 0.63	0.8	41	34	29	25	40	33	29	25	38	32	28	25	37	32	28	25	24	
	否 0.56	1.0	45	39	34	30	44	38	34	30	42	37	33	30	41	36	33	30	29	
		1.25	49	43	39	36	48	43	39	35	46	42	38	35	45	41	37	35	33	
下方投影面積	c m <sup>2</sup>		1.5	52	47	43	39	51	46	42	39	49	45	42	39	47	44	41	38	37
	等価発光面積		c m <sup>2</sup>	2.0	55	51	48	45	55	51	47	45	53	49	47	44	51	48	46	44
取付高さ	器具間隔最大限		2.5	58	54	51	49	57	53	51	48	55	52	50	48	53	51	49	47	46
	H m	横方向 ( A )	縦方向 ( B )	3.0	59	56	53	51	58	55	53	51	56	54	52	50	55	53	51	49
	1.36 H m	1.36 H m	4.0	61	59	56	55	60	58	56	54	58	57	55	53	57	55	54	53	51
			5.0	62	60	58	57	61	59	58	56	60	58	57	55	58	57	56	55	53
			7.0	63	62	61	59	62	61	60	59	61	60	59	58	59	59	58	57	55
			10.0	64	63	62	61	63	62	62	61	62	61	60	60	60	60	59	59	57

