

# 屋内照明器具特性

品番 (品名)	LGB81674	
光源	LDA4 WW- H- E17 / S / 4 ×1	440.0 lm
管理番号	K0187731 (0) DB1	
BZ分類	BZ5 / 1.1 / BZ4	

器具効率	61%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		61%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	3.4	2.6	2.2	1.8	3.3	2.6	2.1	1.8	3.2	2.5	2.1	1.8	3.0	2.5	2.1	1.8	1.7	
	中	0.63	0.8	4.0	3.3	2.9	2.5	3.9	3.3	2.8	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.8	2.5	2.3	
	否	0.56	1.0	4.5	3.8	3.4	3.0	4.4	3.8	3.3	3.0	4.2	3.7	3.3	3.0	4.0	3.6	3.2	3.0	2.8	
	下方投影面積		1.25	4.9	4.3	3.9	3.5	4.8	4.2	3.8	3.5	4.6	4.1	3.8	3.5	4.4	4.0	3.7	3.4	3.3	
等価発光面積		1.5	5.1	4.6	4.2	3.9	5.0	4.6	4.2	3.9	4.9	4.4	4.1	3.8	4.7	4.3	4.0	3.8	3.7		
		2.0	5.5	5.1	4.7	4.4	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	5.0	4.8	4.5	4.3	4.2		
取付高さ	器具間隔最大限		2.5	5.7	5.4	5.1	4.8	5.6	5.3	5.0	4.8	5.4	5.2	4.9	4.7	5.3	5.0	4.8	4.7	4.5	
	横方向 (A)	縦方向 (B)	3.0	5.9	5.5	5.3	5.1	5.8	5.5	5.2	5.0	5.6	5.4	5.1	5.0	5.4	5.2	5.1	4.9	4.7	
Hm	1.35Hm	1.35Hm	4.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.8	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.0	
			5.0	6.1	5.9	5.8	5.6	6.1	5.9	5.7	5.6	5.9	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.2	
			7.0	6.3	6.1	6.0	5.9	6.2	6.1	5.9	5.8	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5	
			10.0	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.1	6.0	6.0	5.9	6.0	5.9	5.9	5.8	5.6	

