

# 屋内照明器具特性

品番 (品名)	L G W 4 5 9 1 0 K	
光源	LDA4 L - H - E17 / S / 4 ×1	440.0 lm
管理番号	K0126468 ( 0 ) DB 1	
B Z 分類	B Z 1 0	

器具効率	67 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		50 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	17 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 ( X0.01 )																Z C M	
保守率	良	0.63	0.6	28	20	15	12	25	18	13	10	18	13	10	7	12	9	6	5	0
	中	0.6	0.8	33	25	20	16	29	22	18	14	21	17	13	10	14	11	9	7	1
	否	0.56	1.0	37	29	24	20	32	26	21	18	24	19	16	13	16	13	10	8	1
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	40	33	28	24	35	29	25	21	26	22	18	16	18	15	12	10	2
			1.5	43	36	31	27	38	32	28	24	28	24	21	18	19	16	14	12	3
取付高さ	器具間隔最大限		2.0	46	41	36	32	41	36	32	28	31	27	24	21	21	18	16	14	4
	横方向 (A)	縦方向 (B)	2.5	49	44	39	36	43	39	35	32	32	29	26	24	22	20	18	16	5
H <sub>m</sub>	H <sub>m</sub>	H <sub>m</sub>	3.0	50	46	42	38	45	41	37	34	34	31	28	26	23	21	20	18	6
			4.0	53	49	45	42	47	43	40	38	35	33	31	29	25	23	22	20	7
			5.0	54	51	48	45	48	45	43	40	37	35	33	31	26	24	23	22	8
			7.0	56	53	51	49	50	47	45	43	38	36	35	33	27	26	25	24	10
			10.0	57	55	53	52	51	49	48	46	39	38	37	36	28	27	26	26	11

