

# 屋内照明器具特性

品番 (品名)	LGB15814															
光源	LDG6L-G/70/W ×1                      725.0 lm															
管理番号	K0190348(1)DB1															
BZ分類	BZ7/0.7/BZ6/1.4/BZ7															

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束	32 % 66 %	室指数	照明率 ( X0.01)                      ZCM																		
保守率	良 中 否	0.67	0.6	47	35	27	22	44	33	26	21	39	30	23	19	34	26	21	17	13	
		0.63	0.8	56	44	35	29	52	41	34	28	46	37	30	26	40	33	27	23	18	
			1.0	61	50	42	35	58	47	40	34	50	42	36	31	44	37	32	28	22	
		0.56	1.25	67	56	48	42	63	53	46	40	55	47	41	36	48	42	37	33	26	
下方投影面積	c m <sup>2</sup>	1.5	71	61	53	47	66	57	50	45	58	51	45	40	51	45	40	36	29		
		2.0	76	67	60	54	72	64	57	52	63	57	52	47	55	50	46	42	34		
取付高さ	器具間隔最大限		2.5	80	72	65	60	75	68	62	57	66	61	56	52	58	54	50	46	38	
	横方向 (A)	縦方向 (B)	3.0	82	75	69	64	78	71	66	61	69	64	59	55	61	57	53	50	41	
H m	1.35 H m	1.35 H m	4.0	86	80	75	70	81	76	71	67	72	68	64	61	64	60	57	54	45	
			5.0	88	83	78	74	83	79	75	71	74	71	67	64	66	63	60	58	47	
			7.0	90	87	83	80	86	82	79	76	77	74	71	69	68	66	64	62	51	
			10.0	93	90	87	84	88	85	83	80	79	77	75	73	70	69	67	65	54	

