

屋内照明器具特性

品番 (品名)	L G W 8 5 0 1 0 F																
光源	LDA4L-H-E17/S/4 ×1 440.0 1 m																
管理番号	K0126467(0)DR1																
BZ分類	BZ8																

器具効率	67 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	34 %																			
下方光束	33 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.63 中 0.6 否 0.56	0.6	30	22	17	13	27	20	15	12	23	17	13	10	18	14	10	8	5	
		0.8	36	27	22	18	32	25	20	17	27	21	17	14	21	17	14	11	7	
		1.0	39	32	26	22	36	29	24	20	30	24	20	17	24	20	17	14	9	
		1.25	43	36	30	26	39	33	28	24	32	27	24	20	26	22	19	17	11	
下方投影面積	c m ²	1.5	46	39	34	29	42	36	31	27	35	30	26	23	28	24	21	19	12	
		2.0	49	43	39	35	45	40	36	32	38	34	30	27	30	27	25	22	15	
		2.5	52	47	42	38	48	43	39	36	40	36	33	30	32	29	27	25	17	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	1.38 H m	1.46 H m	4.0	56	52	48	45	52	48	45	42	43	41	38	36	35	33	31	30	20
			5.0	57	54	51	48	53	50	47	45	45	42	40	38	37	35	33	32	22
			7.0	59	57	54	52	55	52	50	48	46	44	43	41	38	37	36	34	24
			10.0	61	59	57	55	56	54	53	51	48	46	45	44	40	39	37	36	26

