

屋内照明器具特性	
品番 (品名)	LGW85020YU
光源	LDA4L-H-E17/S/4 x1 440.0lm
管理番号	K0122375(1)DB1
BZ分類	BZ10

器具効率	36%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	20%	室指数	床	10%				10%				10%				10%				0%	
下方光束	16%		照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6 中 否 0.56	0.6	1.5	1.1	0.8	0.6	1.4	1.0	0.7	0.5	1.1	0.8	0.6	0.4	0.8	0.6	0.4	0.3	0.1	
	0.8		1.8	1.4	1.1	0.8	1.6	1.2	1.0	0.8	1.3	1.0	0.8	0.6	1.0	0.8	0.6	0.5	0.2		
	1.0		2.0	1.6	1.3	1.0	1.8	1.4	1.2	0.9	1.5	1.2	0.9	0.8	1.1	0.9	0.7	0.6	0.3		
	1.25		2.2	1.8	1.5	1.3	2.0	1.6	1.4	1.2	1.6	1.3	1.1	0.9	1.2	1.0	0.9	0.7	0.4		
下方投影面積	cm ²	等価発光面積	cm ²	1.5	2.4	2.0	1.7	1.4	2.2	1.8	1.5	1.3	1.7	1.5	1.2	1.1	1.3	1.1	1.0	0.8	0.4
				2.0	2.6	2.2	2.0	1.7	2.3	2.0	1.8	1.6	1.9	1.7	1.5	1.3	1.5	1.3	1.1	1.0	0.6
取付高さ	器具間隔最大限		2.5	2.7	2.4	2.2	1.9	2.5	2.2	2.0	1.8	2.0	1.8	1.6	1.5	1.6	1.4	1.3	1.1	0.7	
	横方向 (A)	縦方向 (B)	3.0	2.8	2.5	2.3	2.1	2.6	2.3	2.1	1.9	2.1	1.9	1.7	1.6	1.6	1.5	1.4	1.3	0.7	
H _m	0.00H _m	1.60H _m	4.0	2.9	2.7	2.5	2.3	2.7	2.5	2.3	2.1	2.2	2.0	1.9	1.8	1.7	1.6	1.5	1.4	0.9	
			5.0	3.0	2.8	2.7	2.5	2.8	2.6	2.4	2.3	2.3	2.1	2.0	1.9	1.8	1.7	1.6	1.5	1.0	
			7.0	3.1	3.0	2.8	2.7	2.9	2.7	2.6	2.5	2.4	2.3	2.2	2.1	1.9	1.8	1.7	1.7	1.1	
			10.0	3.2	3.1	3.0	2.9	3.0	2.8	2.7	2.7	2.5	2.4	2.3	2.2	2.0	1.9	1.9	1.8	1.2	

