

屋内照明器具特性

品番 (品名)	L G W 4 5 8 1 0 F	
光源	LDA4 L - H - E17 / S / 4 ×1	440.0 lm
管理番号	K0126468 (0) DB 1	
B Z 分類	B Z 1 0	

器具効率	67 %	天井	80 %				70 %				50 %				30 %				0 %							
	上方光束		50 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
	下方光束		17 %	10 %				10 %				10 %				10 %				0 %						
室指数	照明率 (X0.01)																			Z C M						
保守率	良	0.63	0.6	0.56	0.6	2.8	2.0	1.5	1.2	2.5	1.8	1.3	1.0	1.8	1.3	1.0	0.7	1.2	0.9	0.6	0.5	0				
	中	0.6	0.6	0.56	0.6	3.3	2.5	2.0	1.6	2.9	2.2	1.8	1.4	2.1	1.7	1.3	1.0	1.4	1.1	0.9	0.7	1				
	否	0.56	0.6	0.56	0.6	3.7	2.9	2.4	2.0	3.2	2.6	2.1	1.8	2.4	1.9	1.6	1.3	1.6	1.3	1.0	0.8	1				
下方投影面積 等価発光面積	c m ² c m ²	1.25	1.5	2.0	2.5	4.0	3.3	2.8	2.4	3.5	2.9	2.5	2.1	2.6	2.2	1.8	1.6	1.8	1.5	1.2	1.0	2				
		2.5	3.0	4.0	5.0	4.3	3.6	3.1	2.7	3.8	3.2	2.8	2.4	2.8	2.4	2.1	1.8	1.9	1.6	1.4	1.2	3				
		4.0	5.0	6.0	7.0	4.6	4.1	3.6	3.2	4.1	3.6	3.2	2.8	3.1	2.7	2.4	2.1	2.1	1.8	1.6	1.4	4				
取付高さ	器具間隔最大限		H m	H m	H m	2.5	3.0	4.0	5.0	4.9	4.4	3.9	3.6	4.3	3.9	3.5	3.2	3.2	2.9	2.6	2.4	2.2	2.0	1.8	1.6	5
	横方向 (A)	縦方向 (B)				4.0	5.0	5.3	4.9	4.5	4.2	4.7	4.3	4.0	3.8	3.5	3.3	3.1	2.9	2.5	2.3	2.2	2.0	7		
						5.0	6.0	7.0	8.0	5.4	5.1	4.8	4.5	4.8	4.5	4.3	4.0	3.7	3.5	3.3	3.1	2.6	2.4	2.3	2.2	8
						7.0	8.0	9.0	10.0	5.6	5.3	5.1	4.9	5.0	4.7	4.5	4.3	3.8	3.6	3.5	3.3	2.7	2.6	2.5	2.4	1.0
						10.0				5.7	5.5	5.3	5.2	5.1	4.9	4.8	4.6	3.9	3.8	3.7	3.6	2.8	2.7	2.6	2.6	1.1

